



Contents lists available at ScienceDirect

Chemical Engineering Journal

journal homepage: www.elsevier.com/locate/cej

Review

Geomechanical challenges during geological CO₂ storage: A review
 Youngsoo Song^a, Sungjun Jun^a, Yoonsu Na^a, Kyuhyun Kim^a, Youngho Jang^{b,*},
 Jihoon Wang^{a,c,*}
^a Department of Earth Resources and Environmental Engineering, Hanyang University, Seoul 04763, Republic of Korea^b R&D Planning and Evaluation Division, Korea Institute of Energy Technology Evaluation and Planning, Seoul 06175, Republic of Korea^c Petroleum and Natural Gas Engineering Department, New Mexico Institute of Mining and Technology, Socorro, NM 87801, USA

A B S T R A C T

Carbon capture and sequestration (CCS) method is the only viable method for reducing massive amount of carbon dioxide (CO₂) from the atmosphere to prevent the subsequent environmental and health threats. However, the process is accompanied with geomechanical risks due to the unavoidable pore pressure buildup, such as caprock failure, reactivation of existing faults, poroelastic response of rock and well integrity loss. Not only may the risks lead to undesirable environmental concerns such as CO₂ leakage to the surface, induced seismicity, and surface uplift, but it also would disturb achieving the public's consensus on the CCS process. In this paper, we present an overview of possible geomechanical risks during CCS. We also review the mechanisms and theories of possible geomechanical risks during the CCS and the relevant precedent studies are introduced and described. This study would facilitate understanding the potential geomechanical risks during the CCS and establishing the optimal design of the CCS process to achieve the public acceptance. Some challenges related to handling the geomechanical risks during the CCS are also discussed.

1. Introduction

According to the Paris agreement, 197 countries have reached for the 'low greenhouse gas emissions development' [1], which restricts the greenhouse gas emission of the signees to achieve the global average temperature rise within 1.5 °C above pre-industrial levels. The anthropogenic CO₂ emission will be reduced by the carbon capture, utilization and storage (CCUS) technologies. When the carbon capture and sequestration (CCS), also known as the geological carbon storage (GCS), is adopted, CO₂ is injected and stored in a targeted geologic structure such as depleted hydrocarbon reservoirs, saline aquifers, and underground caverns [2,3]. CCS is the most feasible way to remove and sequester the massive amount of CO₂.

According to the sustainable development scenario projected by International Energy Agency (IEA), at least 650 megatons of the anthropogenic CO₂ is required to be stored annually by 2030 to meet the emission goals. The CO₂ storage capacity of the current large commercial CCS projects is approximately 40 megatons per year, which is only 6 % of the desired amount [4]. In the same manner, the South Korea government plans to reduce the CO₂ emission by 40 % business as usual (BAU) in 2030 and achieve the net-zero by 2050. The amount of CO₂ sequestered by the CCS process is expected as at least 55 megatons, 69

% of the total CO₂ reduction until 2050 [5]. One of the target geologic structure is the depleted Donghae gas reservoir in East Sea, which is planned to be repurposed for the CO₂ storage, where 0.4 megaton of CO₂ per year are expected to be geologically stored from 2025 [6].

When CO₂ is injected and stored into an underground geological structure, the pore pressure buildup is unavoidable. The change of the pore pressure redistributes the stress status and induces the poroelastic responses at the caprock and target formation [7–10]. If severe, it may lead to geomechanical hazards such as leakage of the injected CO₂, surface uplift, and induced seismicity, which are major environmental concerns during the CCS project. In addition, the well integrity should be considered because the injected CO₂ could be leaked through any component of the well what was designed to be used as the flowing path. Uncontrolled release of injected fluid can shorten life cycle of the well and it may lead to CO₂ leakage. Therefore, establishment of the optimal CCS design considering the geomechanical risks is important to perform the environmentally safe project and to achieve the public acceptance [11].

There are geomechanical risks during a CCS process, but investigations of causes, mechanisms and post-analysis methods have not yet been conducted [12]. In this paper, geomechanical risks potentially caused by the pore pressure buildup due to the CO₂ injection will be

* Corresponding authors at: Department of Earth Resources and Environmental Engineering, Hanyang University, Seoul 04763, Republic of Korea & Petroleum and Natural Gas Engineering Department, New Mexico Institute of Mining and Technology, Socorro, NM 87801, USA (J. Wang); R&D Planning and Evaluation Division, Korea Institute of Energy Technology Evaluation and Planning, Seoul 06175, Republic of Korea (Y. Jang).

E-mail addresses: jangyh@ketep.re.kr (Y. Jang), jihoonwang@hanyang.ac.kr (J. Wang).

<https://doi.org/10.1016/j.cej.2022.140968>

Received 9 December 2022; Accepted 12 December 2022

Available online 17 December 2022

1385-8947/© 2022 The Author(s). Published by Elsevier B.V. This is an open access article under the CC BY license (<http://creativecommons.org/licenses/by/4.0/>).